



# GXP1630

## A Small Business Gigabit IP Phone

The GXP1630 is a powerful IP phone for small-to-medium businesses (SMBs). This Linux-based model includes 3 lines, 3 XML programmable soft keys, 8 BLF keys and 4-way conferencing. A 132x64 backlit LCD screen creates a clear display for easy viewing. Additional features such as dual switched gigabit network ports, HD audio, multi-language support, integrated PoE and call-waiting allow the GXP1630 to be a high quality, versatile and dependable office phone.



**3 LINES**  
 3 lines, 3 SIP accounts, 3 call appearances, 3 softkeys



**Gigabit**  
 Dual-switched auto-sensing 10/100/1000mbps network ports



Includes 8 dual-colored BLF/speed dial keys



Built-in PoE to power the device and give it a network connection



HD audio to maximize audio quality, full-duplex speakerphone



Use with Grandstream's UCM series of IP PBXs for Zero Config provisioning



Electronic Hook Switch (EHS) support for Plantronics headsets



Automated provisioning options include TR-069 and XML config files



TLS and SRTP security encryption technology to protect calls and accounts



**4 WAY**  
 4-way audio conferencing for easy conference calls

|  |  |
|--|--|
| <b>Protocols/Standards</b>               | SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP  |
| <b>Network Interfaces</b>                | Dual switched auto-sensing 10/100/1000 Mbps Ethernet ports, integrated PoE   |
| <b>Graphic Display</b>                   | 132 x 64 backlit graphical LCD display   |
| <b>Feature Keys</b>                      | 3 line keys with dual-color LED and 3 SIP accounts, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys, 8 BLF keys, 13 dedicated function keys for MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME, PHONEBOOK, MESSAGE, HOLD, PAGE/INTERCOM, RECORD, HOME  |
| <b>Voice Codexs</b>                      | Support for G.711 $\mu$ /a, G.722 (wide-band), G.723(pending), G.726-32, G.729 A/B, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO)   |
| <b>Telephony Features</b>                | Hold, transfer, forward (unconditional/no-answer/busy), call park/pickup, 4-way conference, shared-call-appearance (SCA) / bridged-line-appearance (BLA), downloadable phone book (XML, LDAP, up to 500 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & fail-over |
| <b>Headset Jack</b>                      | RJ9 headset jack (allowing EHS with Plantronics headsets)  |
| <b>HD Audio</b>                          | Yes, HD handset and speakerphone with support for wideband audio   |
| <b>Base Stand</b>                        | Yes, 2 angled positions available, wall mountable  |
| <b>Headset Jack</b>                      | Yes  |
| <b>QoS</b>                               | Layer 2 QoS (802.1Q, 802.1P) and Layer 3 QoS (ToS, DiffServ, MPLS)   |
| <b>Security</b>                          | User and administrator level access control, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control  |
| <b>Multi-language</b>                    | English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more  |
| <b>Upgrade/Provisioning</b>              | Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file   |
| <b>Power and Green Energy Efficiency</b> | Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mAPoE: IEEE802.3 af Class 2, 3.84W-6.49W   |
| <b>Physical</b>                          | Dimension: 222.5mm (L) x 208.5mm (W) x 76.2mm (H) (with handset) Unit weight: 0.8kg; Package weight: 1.2kg   |
| <b>Temperature and Humidity</b>          | Operation: 0°C to 40°C, Storage: -10°C to 60°C , Humidity: 10% to 90% Non-condensing   |
| <b>Package Content</b>                   | GXP1630 phone, handset with cord, base stand, universal power supply, network cable, Quick Installation Guide, brochure, GPL License   |
| <b>Compliance</b>                        | FCC: Part 15 (CFR 47) Class BCE : EN55022 Class B, EN55024 Class B; EN61000-3-2, EN61000-3-3, EN60950-1RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/NZS 60950.1  |