
Comfort calls

DW Pro1



- Unique Premium Design Crafted for comfort
- High Comfort Wearing Style Perfect adjustment to your ear for a full day wearing comfort
- Intuitive User Interface Mute microphone and adjust volume up or down
- Boosted Productivity Ultra noise-canceling microphone filters out unwanted background noise
- Sennheiser HD Voice Clarity Wideband sound for a more natural experience
- Full Workday Talk Time 8 hours in wideband sound mode and 12 hours in narrowband sound mode
- Intelligent Fast Charging 50% in 20 minutes gives you 4 hours talk time
- Long Distance Wireless Range Up to 55 m in typical office building. Up to 180 m in line of sight
- Protected Hearing ActiveGard[™] technology protects against acoustic shock and sudden sound surges
- Desk Phone & Softphone Switch from one communication channel to the other. One touch on the base station to select the channel you wish to call from
- Intuitive & Easy pairing For desk sharing and phone conferencing



Imagine making every call in comfort, and being able to focus on what's important: the conversation.

DW Pro1 connects to both desk phone and softphone.





Specifications

Headset	Order name	Art. No.	EAN No.	UPC No.		
DW Pro1	DW 20 – EU	504304	40 44155 05038 7	6 15104 17955 4		
DW Pro1	DW 20 – UK	504305	40 44155 05039 4	6 15104 17956 1		
DW Pro1	DW 20 – US	504306	40 44155 05040 0	6 15104 17957 8		
DW Pro1	DW 20 – AUS	504307	40 44155 05041 7	6 15104 17959 2		
Technology						
DECT for EU, UK, A	US	DECT CAT-iq (1.880 to 1.900 MHz)				
DECT for US		DECT 6.0 (1.920 to 1.930 MHz)				
GAP compatible		Yes (Headset)				
Headset		Connect to Ba				
Base Station				000		
Base Station		Connect to de	esk phone and softph	lone		
EHS (Electronic Ho	EHS (Electronic Hook Switch)		ry – order EHS adapte	er separately)		
Mechanical Hook I	Lifter	HSL 10 (acce	ssory – order separat	ely)		
Soft phone call co	ntrol Software	HeadSetup (i	ncluded on CD)			
Microsoft Commu	nicator compatible	Yes				
Technical data						
Operational temp	perature range	+5 °C to + 45 °C (+41 °F to +113 °F)				
Storage temperat	0	-20 °C to + 70 °C (-4 °F to +158 °F)				
Weight Headset	5	65 g				
Ear pad size		ø 50 mm / 1.96 inches				
Battery (Lithium Polymere) exchangeable		Yes - for service (see manual)				
Personalization		Yes - with nameplate on headset				
			•			
Package dimensions (H x W x D)		16.5 cm x 16 cm x 16 cm				
Package weight		950 g				
Units in distribute		8				
Master carton dimensions (H x W x D)		36 x 38 x 38 cm				
Master carton weight		8.93 kg				
Range – line of sight		180 m				
Range – in typical office building		55 m				
Automatic power adjustment		Yes (distance between HS and Base)				
Talk time in Wideband Mode		Up to 8 hours				
Talk time in Narrowband Mode		Up to 12 hours				
Stand by time		Up to 100 Hours				
Auto – headset OFF when out of range		Yes - after 30 minutes				
Charge time 0 – 50%		20 minutes				
Charge time 0 – 100%		1 hour				
		Maa saa k				
Headset Auto Lin	k to Base	Yes - can be a	activated on the base	station		



Specifications

Microphone Electret Condenser Microphone, Ultra noise-cance						
•		Electret Condenser Microphone, Ultra noise-canceling				
Frequency response Wig Frequency response Nar		150 Hz – 6.8 KHz 300 Hz – 3.5 KHz				
Mute Microphone	Yes					
· · ·						
Speaker	Neodyn	Neodynium Magnet Speaker				
Frequency response Wie		150 Hz – 6.8 KHz				
Frequency response Nar		300 Hz – 3.5 KHz				
All acoustic parts observ	ve the IIA-920	wideband s	standards			
Safety						
Automatic Acoustic Sho	YES - Ad	YES - ActiveGard™				
EU/AU Limiter		YES - Ad	YES - Activation by dip switch			
Delivery content						
Headset						
Base Station						
Power supply						
USB cable						
Audio phone cable						
Printed QuickGuide						
• CD with Manual, QuickGuide, nameplate t			late and HeadSetup In	stallation Program		
Printed safety guid	e					
Accessories NEW						
Product description	Order name	Art. No	EAN No.	UPC No.		
EHS Avaya adapter	CEHS-AV 01	504100	40 44155 04738 7	6 15104 17407 8		
EHS Snom adapter	CEHS-SN 01	504101	40 44155 04739 4	6 15104 17408 5		
EHS Alcatel adapter	CEHS-AL 01	504102	40 44155 04740 0	6 15104 17422 1		
EHS Cisco adapter	CEHS-CI 01	504103	40 44155 04741 7	6 15104 17423 8		
EHS Polycom adapter	CEHS-PO 01	504104	40 44155 04742 4	6 15104 17424 5		
EHS DHSG adapter	CEHS-DHSG	504105	40 44155 04743 1	6 15104 17425 2		
Accessories EXISTING						
Product description	Order name	Art. No	EAN No.	UPC No.		
Handset Lifter	HSL 10	500712	40 44155 04738 7	6 15104 17407 8		
Interface box for						
telephones featuring	TCI 01	500275	40 44155 04739 4	6 15104 17408 5		
electronic hook switch						



Specifications

Single components/spare parts Available from October

Headset and base station can be purchased separately. This allows a 2nd headset to be added to any DW Series base station or used as a spare.

Product description	Order name	Art. No	EAN No.	UPC No.
Single headset of DW 20	DW 20 HS	504325	40 44155 05059 2	6 15104 17997 4
DW Base set for DW series	DW BS-EU	504330	40 44155 05064 6	6 15104 18004 8
DW Base set for DW series	DW BS-UK	504331	40 44155 05065 3	6 15104 18006 2
DW Base set for DW series	DW BS-US	504332	40 44155 05066 0	6 15104 18007 9
DW Base set for DW series	DW BS-US	504333	40 44155 05067 7	6 15104 18008 6

Base including power supply, audio cable and USB cable

Spare parts **EXISTING**

- Power supply US
- Power supply AUS
- Power supply UK
- Power supply EU

Spare parts Available from October

- Ear pad
- Name plate set Pro 1/2
- Audio cable RJ 45 RJ 9
- USB cable

Type approvals

i ype approvais	
Europe	EMC - EN 301489-6
CE	RADIO - EN 301406
	Safety - EN 60950-1
	SAR (headset) - EN 50360 ref. EN 62209-1
USA:	This product meets the safety requirements of CSA No. 231437
Approved by	
Canada:	Industry Canada RSS 213 Issue 2
	IC ID 2099 D-TDB1 (base station)
	IC ID 2099 D-TDH1 (headset)
USA:	FCC 47 CFR Part 15 (d)
	FCC ID: DMOCDBDIB (base station)
	FCC ID: DMOCDHDFC (Pro 1 headset)
	FCC ID: DMOCDHDEC (Pro 2 headset)
Australia	AS/ACIF S004

