

T22P



T22P is the ideal IP business phone to equip the office for reliable, intensive telephone based business without incurring extravagant expense. Productivity driven, this best selling mid range phone is a robust, hard working favourite.



T22P

Network Features

Info

SIP v1(RFC2543), v2(RFC3261) 3 User accounts NAT Transverse: STUN mode IP Assignment: Static/DHCP/PPPoE In-Band DTMF, Out-of-Band DTMF, SIP

Proxy mode and Peer-to-peer SIP link mode

TFTP/DHCP/PPPoE client Telnet/HTTP server DNS client NAT/DHCP server Support VLAN, QoS PoE optional

Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM VAD, CNG, AEC, PLC, AJB, AGC Full-duplex hands-free speakerphone

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward Caller ID, Call List, DND, Redial, Flash 3-way Conference, Speed Dial Personal Ring Tone, Voicemail Volume Adjustment, Mute, Speakerphone

IP PBX System Integration

Dial Plan, Dial-now, Paging Downloadable enterprise phonebook Call Park, Call Pickup, Distinctive Ringtone Auto-answer, intercom

Config, Upgrade and Usage

Language Customization Support Firmware Upgrade: TFTP/Console/Autoprovision Auto-provision: TR069 Optional Direct IP call without SIP proxy Dial number via SIP server Dial URL via SIP server

Security

Secure RTP Digest authentication using MD5/MD5-Secure configuration file via AES encryption

Physical Features

TI Titan Chipset LCD: 132x64 with blue backlit 3 programmable keys, 4 text-sensitive keys 23 hard keys, 2 indication LEDs

Headset port: RJ9 Network Interface: 2xRJ45 10/100M

ports Dimension: 275 x 220 x105 mm

Net Weight: 1.22 kg Power adapter: Input: AC 100~240V

Output: DC 5V/1A Operating humidity: 10~95% Storage temperature: up to 60 C

Package Features

Qty per Carton: 10 Carton Weight: 13.3 Kgs Carton Dims: 565 x 570 x 255 mm

Certifications

WEEE









